


TRI-CAP™

TECHNICAL DATA				
DIMENSIONS (W x H x D)	CAPACITY (CFM)	MEDIA AREA (SQ FT)	INITIAL RESISTANCE ("WG)	
			ONE PLY	TWO PLY
12 x 24 x 9	750	6.0	0.09	0.14
16 x 20 x 9	800	7.5	0.09	0.14
20 x 20 x 9	1000	8.0	0.09	0.14
16 x 25 x 9	1000	8.0	0.09	0.14
20 x 24 x 9	1200	9.0	0.09	0.14
20 x 25 x 9	1200	9.0	0.09	0.14
24 x 24 x 9	1500	12.0	0.09	0.14
12 x 24 x 15	1250	10.0	0.17	0.24
20 x 20 x 15	1750	12.5	0.17	0.24
20 x 24 x 15	2000	15.0	0.17	0.24
20 x 25 x 15	2000	15.0	0.17	0.24
24 x 24 x 15	2500	20.0	0.17	0.24


TRI-CAP CARTRIDGES are extended surface filters constructed of progressive density synthetic media available in both one and two-ply. TRI-CAP TWO PLY – 45% Average Efficiency – constructed of two layers, a prefilter layer and a final more efficient layer. TRI-CAP ONE PLY – 30% Average Efficiency. Recommended Final Resistance is 0.75" W.G. To fit Cambridge "Hi-Cap" and "Glass Cap" Frames†.

TECHNICAL DATA					
DIMENSIONS W x H x D	CAPACITY CFM	TRI-FLO RESISTANCE ("WG)		TRI-FLO P RESISTANCE ("WG)	
		INITIAL	FINAL	INITIAL	FINAL
12 x 24 x 10	900	0.21	1.0	0.12	1.0
24 x 24 x 10	1800	0.21	1.0	0.12	1.0
12 x 24 x 15	1100	0.26	1.0	0.15	1.0
16 x 20 x 15	1200	0.26	1.0	0.15	1.0
16 x 25 x 15	1450	0.26	1.0	0.15	1.0
20 x 20 x 15	1450	0.26	1.0	0.15	1.0
20 x 25 x 15	1800	0.26	1.0	0.15	1.0
24 x 24 x 15	2200	0.26	1.0	0.15	1.0
12 x 24 x 18	1250	0.32	1.0	0.20	1.0
24 x 24 x 18	2500	0.32	1.0	0.20	1.0
12 x 24 x 22	1500	0.34	1.0	0.25	1.0



TRI-FLO™

TRI-FLO CARTRIDGES – 45% Average Efficiency – are constructed of micro-glass media. TRI-FLO P CARTRIDGES – 25% Average Efficiency – are constructed of synthetic media. To fit Cono 45 and Cono Pac 45 Frames without any modifications†.



TRI-P™

TECHNICAL DATA										
SIZE	CAPACITY (CFM)		INITIAL RESISTANCE ("WG)			FINAL RESISTANCE ("WG)			MEDIA AREA (Sq. Ft.)	
	W x H x D	TP200	TP15	TP200	TP100	TP15	TP200	TP100		TP15
12x24x8	450		900	0.40	0.25	0.35	0.90	0.80	0.80	14.5
16x20x8	510		1025	0.40	0.25	0.35	0.90	0.80	0.80	15.8
20x20x8	600		1200	0.40	0.25	0.35	0.90	0.80	0.80	19.8
20x25x8	775		1500	0.40	0.25	0.35	0.90	0.80	0.80	25.6
24x24x8	920		1725	0.40	0.25	0.35	0.90	0.80	0.80	29.0
12x24x12	630		1025	0.40	0.25	0.35	0.90	0.80	0.80	20.9
24x24x12	1200		2000	0.40	0.25	0.35	0.90	0.80	0.80	41.8
12x24x24	1000		N/A	0.55	0.40	N/A	1.0	0.90	N/A	48.6
24x24x24	2000		N/A	0.55	0.40	N/A	1.0	0.90	N/A	96.0

TRI-P CARTRIDGES offer medium to high efficiency and are constructed of pre-pleated media bonded to kraft fiberboard. To fit Camfil Farr HP Series, Glide/Pack® and Hi Kleen Frames without any modifications†.

PERFORMANCE DATA			
MODEL #	TP15	TP100	TP200
Efficiency	55-65%	80-85%	90-95%

Tri-Dim Filter Corporation is committed to continual product development – all descriptions, specifications and performance data are subject to change without notice. Tri-Dim products are manufactured to exacting criteria - there can be a ±5% variance in filter performance. Tri-Dim® and Tri-Dek® are Registered Trademarks of Tri-Dim Filter Corporation. Tri-Cap™, Tri-Flo and Tri-P are Trademarks of Tri-Dim Filter Corporation. †Trade Names used for identification purposes only.



TRI-DIM FILTER CORPORATION
 P.O. BOX 466 • 93 INDUSTRIAL DRIVE
 LOUISA, VA 23093
 (540) 967-2600 • FAX: (540) 967-2835
 EMAIL: info@tridim.com • Website: www.tridim.com
TOLL FREE 1-800-458-9835



Local Representation:

Brochure # 800-2
 Revision: 03/2008



PLEASE RECYCLE - This paper may not be recyclable in your area if facilities do not exist. This brochure is printed on paper that is certified by the Sustainable Forestry Initiative (SFI) - for more information go to www.sfi.org.

